



Teléfono IP Wi-Fi Inalámbrico WP822

El WP822 es un teléfono IP Wi-Fi portátil diseñado para adaptarse a una variedad de empresas y aplicaciones de mercados verticales, incluyendo tiendas, logística, salud y seguridad. Este teléfono Wi-Fi para empresas viene equipado con Wi-Fi 802.11a/b/g/n/ac de doble banda integrado, un diseño avanzado de antena y soporte de roaming. Al agregar un tiempo de conversación de 8 horas, voz HD con micrófonos duales y un botón configurable de micrófono, el WP822 viene equipado con una combinación de características, movilidad y durabilidad para satisfacer todas las necesidades de telefonía portátil.



Wi-Fi de doble banda con diseño avanzado de antena y soporte de roaming eficiente



2 cuentas SIP, 2 líneas



Diseño de voz HD y micrófonos duales con AEC y tecnología Noise Shield



Batería recargable de 2000 mAh, tiempo de conversación de 8 horas, tiempo en reposo de 200-horas



Bluetooth integrado para conectar los audífonos



Botón configurable de micrófono



Puerto micro USB y conector para audífonos de 3.5 mm

Protocolo/Estándares	SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, SSH, TFTP, NTP, STUN, SIMPLE, 802.1x, TLS, SRTP, IPv6
Códex de Voz y Capacidades	Support for G.711µ/a, G.729A/B, G.722 (wide-band), iLBC, Opus, in-band and out-of-band DTMF (In audio, RFC2833, SIP INFO), VAD, CNG, AEC, PLC, AJB, AGC, ANS
Wi-Fi	Yes, integrated dual-band Wi-Fi 802.11 a/b/g/n/ac (2.4GHz & 5GHz). 802.11r Supported (WPA2/WPA2-Enterprise).
Cifrado Wi-Fi	WEP, WPA/WPA2, WPA Enterprise, WPA3, WPA3-Enterprise
Pantalla	2.4 inch (240x320) TFT color LCD
Bluetooth	Yes, integrated
Periféricos	3 soft keys, dial, hang-up, speakerphone, phonebook, backlit keypad, proximity sensor, vibration motor, volume button, navigation keys, and accelerometer supporting configurable gestures
Botón de Micrófono	Customizable button for push-to-talk
Puertos Auxiliares	3.5 mm headset jack, Micro USB port for charging, dual-MIC, dual-color MWI LED
Telefonía	Hold, transfer, forward, 3-way audio conference, call waiting, call log (up to 100 records), downloadable phonebook (XML, up to 500 items) off-hook auto dial, auto answer, flexible dial plan, personalized music ringtones, server redundancy and fail-over, push to talk, LDAP
Seguridad	User and administrator level passwords, MD5 and MD5-sess based authentication, 256-bit AES based secure configuration file, SRTP, TLS, 802.1x media access control
Audio HD	Yes, both on handset and speakerphone with support for wideband audio, HAC supported
QoS	802.11e (WMM) and Layer 3 (ToS, DiffServ, MPLS) QoS
Múltiples Idiomas	English, Chinese, German, French, Italian, Portuguese, Russian, Spanish, and more
Actualización/Aprovisionamiento	Firmware upgrade via TFTP/HTTP/HTTPS/FTP/FTPS, mass provisioning using encrypted XML configuration file, manual upload
Alimentación y Eficiencia de Energía Limpia	Universal power adapter included Input: 100-240VAC; Output: +5VDC, 1A (5W) 2000mA Li-ion battery, 200h standby time and 8h talk time
Características Físicas	Handset dimensions: 164.0 x 52.0 x 25.8mm Charger cradle dimensions: 77.9 x 81.2 x 38.2mm Handset weight: 185.90g Handset package weight (not including QIG): 422.60g
Temperatura y Humedad	Operating Temperature: 0°C to 45°C; Operating Humidity: 10-90% (non-condensing) Storage Temperature: -20°C to 60°C; Storage Humidity: 10-90% (non-condensing)
Contenido del Paquete	Handset unit, universal power supply, charger cradle, belt clip, 1 Li-ion battery, Quick Start Guide
Conformidad	FCC, CE, RCM, IC, UKCA